

PURCLEAN™

SPOT-FREE RINSE SYSTEMS

NEWWAVE™
INDUSTRIES

Lot Master Spot-Free Rinse System

Features



- ◆ Water Stabilizer (replaces softener)
- ◆ Pump Pressure Gauges
- ◆ Carbon Tank
- ◆ Multi-Stage Pressure Pump
- ◆ Low Pressure Shut Off
- ◆ Automatic Membrane Flush
- ◆ Production & Reject Meters
- ◆ Water Quality Indicator
- ◆ Two Step Powdercoated Frame
- ◆ Repressurization Pump
- ◆ Thin Film Membrane
- ◆ ETL Listed

Specifications	LotMaster Spot-Free Rinse System
Water Requirements	(1) 1" Water line w/ FPT ball valve, 20 GPM at 30 PSI. Mount 4 feet up from floor to the right of the spot free rinse system and (1) drain.
Electrical Requirements	(2) 120V 20 Amp circuit with its own 110V receptacle. Put plug 5 feet up from the floor to the right of the spot free rinse system
RO Output	Production - 1.4 GPM
Reject	1.6 GPM
RO Motor	1 HP Flint & Walling booster pump
RO Motor Amps	110-120V = 18amps
Dimensions	24" Wide X 48" Tall X 12.5" Deep
Net Weight	300 Lbs.
Delivery Pump	27 GPM Low pressure transfer pump