





OIL FIRED PORTABLE PRESSURE WASHER | Specifications:

	GENERAL					ELECTRICAL			BURNER SYSTEM		DIMENSIONS/WEIGHT			
Model	Туре	GРM	PSI	HP	Drive	Volt	Amp	Ph	ВТИ	Stack Size		W	i.	Lb
12-203D	ED	2	300	.75	Direct	115	20	1	179,000	8"	31.5"	24.5"	39"	290
12-212	ED	2	1200	2	Direct	120	20	1	175,000	7"	31.5"	24.5"	39"	300
12-320D	ED	3	2000	4	Direct	230	20	1	269,000	7"	31.5"	24.5"	39"	320
12-303D	ED	3	300	.75	Direct	115	15	1	383,000	8"	37.5"	29"	44.5"	380
12-210CD	ED	2.2	300/1000	1.5	Direct	115	20	1	383,000	8"	37.5"	29"	44.5"	415
12-216	ES/EL	2	1600	2.3	Belt	120	20	1	175,000	7"	31.5"	24.5"	39"	310
12-310	ES/EL	3	1000	2.3	Belt	115	20	1	269,000	7"	31.5"	24.5"	39"	310
12-325	ES/EL	3	2500	5	Belt	230	20	1	269,000	7"	31.5"	24.5"	39"	325
12-416	ES/EL	4	1600	4	Belt	230	20	1	384,000	8"	37.5"	29"	44.5"	540
12-423	ES/EL	4	2300	6	Belt	230	30	1	384,000	8"	37.5"	29"	44.5"	465
12-430	ES/EL	4	3000	8	Belt	230	40	1	384,000	8"	37.5"	29"	44.5"	485

Features (not shown on breakout);

ED Model Features:

- · Heavy Duty Electro Plated Fittings
- Built-In Hose Reel Socket
- 3/8" x 40' High Pressure Hose
- · Four Wheel Design
- ASTM A53 Schedule 80 Steel Heating Coil
- Fuel Oil Solenoid
- In-Line Fuel Filter
- Trigger Gun Control
- 36" Insulated Wand

· Flood Nozzle w/Fixed 15° Spray Tip

GFCI Protection w/10' Electrical Cord

ES - Includes All the Features of ED Plus: Belt Driven Pump

- · Exclusive High Strength Nylon Manifold
- Quick Couple Manifold Plumbing Connections
- · Polyethylene Fuel Tank w/Chemical Metering
- · 0° & 15° Quick Couple Nozzles

EL - Includes All the Features of ED Plus:

- · Stainless Steel Belt Guard & Wrapper
- Stainless Steel Electrical Control Panel
- · Water Separating Fuel Filter
- 3/8" x 50' High Pressure Hose
- · GFCI Protection w/36'Electrical cord (except 12-430)
- · In-Line Fuel Shutoff
- · Accessory Package



A Closer Look at the Features:



Molded Poly Fuel Tank Prevents saving costly replacement



Heavy Duty Welded Frame Prevents frustration due to oose bolts & rusty



High Limit Temp. Control Protects the system from overheating & causing costly repairs.



Direct/Belt Drive Triplex Pump Lower maintenance cos due to long life & durability.



Pressure Relief Valve Prevents injury & cost due to an over-pressurized system.



Exclusive Coil Design Heats wate



High Efficiency Insulation System Keeps the heat vhere it belongs e heat chamber



High Efficiency Burner Conserve fuel & your



comes first.

GFCI Cord Protection Makes sure your safety



Soap Control (ES-EL) Allows for the precise metering of your expensive soap



Heavy Duty Electric Motor Built strong to handle your toughest demands.



Pneumatic Tires On dish wheels for mobility



Configured for you by:

