

<b>Flow Rate</b>	2 gpm
<b>Pressure</b>	1600 psi
<b>Motor Voltage</b>	115 v
<b>Phase</b>	1
<b>Amp Requirement</b>	20 amp
<b>Motor Power</b>	2.3 hp
<b>Fuel Source</b>	Kerosene, #1, #2 Diesel
<b>Fuel Consumption</b>	1.25 gal/h
<b>Fuel Tank Capacity</b>	4.5 gal
<b>BTU Rating</b>	175000 Btu
<b>Pump Style</b>	Oil Bath Crankcase Triplex Ceramic Plunger
<b>Coil Type</b>	Schedule 80
<b>Coil Construction Type</b>	Hydro insulated cold water wrap
<b>Coil Length</b>	96 ft
<b>Float Tank Construction Material</b>	Anti-Corrosive Poly
<b>Fuel Tank Construction Material</b>	Anti-Corrosive Poly
<b>Optional Parts/Features</b>	Temperature Control
<b>Chemical Features</b>	High Pressure Precise Metered
<b>Manufacturing Notes</b>	All 115 volt units have ground fault interrupters standard. Motor/Voltage: Special voltages on request.
<b>Exhaust Stack</b>	8 in
<b>Length</b>	40 in
<b>Width</b>	27 in
<b>Height</b>	40 in
<b>Weight</b>	420 lbs