





## OIL FIRED PORTABLE PRESSURE WASHER | Specifications:

			NEW WALLSHAM SHAME		-				-					
		GEN	GENERAL			ELECTRICAL			BURNER SYSTEM		DIMENSIONS/WEIGHT			
Model	Туре	GРM	PSI	HP	Drive	Volt	Amp	Ph	BTU	Stack Size	L	w	9	Lb
12-203D	ED	2	300	.75	Direct	115	20	1	179,000	8"	31.5"	24.5"	39"	290
12-212	ED	2	1200	2	Direct	120	20	1	175,000	7"	31.5"	24.5"	39"	300
12-320D	ED	3	2000	4	Direct	230	20	1	269,000	7"	31.5"	24.5"	39"	320
12-303D	ED	3	300	.75	Direct	115	15	1	383,000	8"	37.5"	29"	44.5"	380
12-210CD	ED	2.2	300/1000	1.5	Direct	115	20	1	383,000	8"	37.5"	29"	44.5"	415
12-216	ESEL	2	1600	2.3	Belt	120	20	1	175,000	7"	31.5"	24.5"	39"	310
12-310	ES/EL	3	1000	2.3	Belt	115	20	1	269,000	7"	31.5"	24.5"	39"	310
12-325	ES/EL	3	2500	5	Belt	230	20	1	269,000	7"	31.5"	24.5"	39"	325
12-416	ES/EL	4	1600	4	Belt	230	20	1	384,000	8"	37.5"	29"	44.5"	540
12-423	ES/EL	4	2300	6	Belt	230	30	1	384,000	8"	37.5"	29"	44.5"	465
12-430	ES/EL	4	3000	8	Belt	230	40	1	384,000	8"	37.5"	29"	44.5"	485

### Features (not shown on breakout):

#### **ED Model Features:**

- · Heavy Duty Electro Plated Fittings
- · Built-In Hose Reel Socket
- 3/8" x 40' High Pressure Hose
- Four Wheel Design
- ASTM A53 Schedule 80 Steel Heating Coil
- · Fuel Oil Solenoid
- · In-Line Fuel Filter
- · Trigger Gun Control
- · 36" Insulated Wand

#### · Flood Nozzle w/Fixed 15° Spray Tip

GFCI Protection w/10' Electrical Cord

## ES - Includes All the Features of ED Plus:

- Belt Driven Pump
- Exclusive High Strength Nylon Manifold
- Quick Couple Manifold Plumbing Connections
- Polyethylene Fuel Tank w/Chemical Metering
- 0° & 15° Quick Couple Nozzles

### EL - Includes All the Features of ED Plus:

- · Stainless Steel Belt Guard & Wrapper
- · Stainless Steel Electrical Control Panel
- · Water Separating Fuel Filter
- 3/8" x 50' High Pressure Hose
- · GFCI Protection w/36'Electrical cord (except 12-430)
- · In-Line Fuel Shutoff
- Accessory Package



# A Closer Look at the Features:



Molded Poly Fuel Tank Prevents corrosion saving costly replacement



Heavy Duty Welded Frame Prevents frustration due to loose boits & rusty wear points.



High Limit Temp. Control Protects the system from overheating & causing costly Direct/Belt Drive



Triplex Pump maintenance costs due to long life & durability.



Pressure Relief Valve Prevents injury & cost due to an over-pressurized system.



Exclusive Coil Design Heats water



High Efficiency Insulation System Keeps the heat vhere it belongs e heat chamber



High Efficiency Burner Conserve

fuel & you



**GFCI Cord** Protection Makes sure your safety comes



 Soap Control (ES-EL) Allows for the precise metering of your expensive soap.



Stainless Steel Nozzles Panel mounted to be handy & accessible



Heavy Duty Electric Motor Built strong to handle your toughest demands.



Pneumatic Tires On dish wheels for mobility





